

Non-topcoated, 800-sensitivity black image product for general printer applications.

GAMING PRODUCTS



KEY FEATURES


- 800-sensitivity
- Press printable front and back
- Barcode graphics and imaging


APPLICATIONS


- Tote/wagering
- Tickets

PRODUCT CHARACTERISTICS

Caliper (mils/µm)	$3.8 \pm 0.35/97 \pm 9$
Basis Weight	
17 x 22—500 (lbs)	23.3 ± 1.2
g/m2	87.6 ± 4.5
Thermal Response - Nominal	
Static (°C ± 5°)	
0.2 ODU	85
1.0 ODU	132
Maximum Density (ODU)	1.3
Temperature Required	149
Dynamic—Atlantek 400 (mJ/mm2)	
0.2 ODU	5.3
1.0 ODU	7.9
Maximum Density (ODU)	1.87
Energy Required	14.6
Brightness (UV Included)	>86
Gurley Stiffness Nominal (mg)	MD 140
	CD 75
Elmendorf Tear Nominal (g)	MD 51
	CD 56
Tensile (lbs/in)	MD 31
	CD 15
Parker Print Surface	<1.40







*Designed specifically for use in weigh scale applications. Other applications will need further validation. Limited capabilities for wet applications. Use of Appvion's direct thermal products in processing, equipment, end-use, or other applications for which they were not intended voids all warranties.

