This midweight, direct thermal product is an 820-sensitivity, black image grade for chart, retail and printer applications. Suited for flexographic and UV litho printing on front and back. Produced without the use of BPA.

SPECIALTY RETAIL PRODUCTS



KEY FEATURES

- Bond-like feel
- Press printable front and back
- * Bar code and graphics imaging
- Bright white appearance
- BPA Free

APPLICATIONS

- Wide format chart/plotter
- Kiosks
- Parking
- Portable printers

PRODUCT CHARACTERISTICS

Caliper (mils/µm)	3.20 ± 0.15/81.2 ± 3.8
Basis Weight 17 x 22—500 (lbs) g/m2	19.6 ± 1.1 73.7 ± 4.0
Thermal Response - Nominal Static (°C ± 5°)	
0.2 ODU	79
1.0 ODU	110
Maximum Density (ODU)	1.53
Temperature Required	135
Dynamic—Atlantek 400 (mJ/mm2)	
0.2 ODU	4.6
1.0 ODU	7.5
Maximum Density (ODU)	1.8
Energy Required	16
Brightness (UV Excluded)	>74
Gurley Stiffness Nominal (mg)	MD 90 CD 40
Elmendorf Tear Nominal (g)	MD 43 CD 44
Tensile (lbs/in)	MD 32 CD 16
Parker Print Surface	<1.30





